BODY BIKE Supreme

Max user hight 220 cm / 7.2 ft **Max user weight** 150 kg / 331 lbs **Q-factor** 168 mm / 6.6 in



KEY SPECIFICS

Hight	99 cm	Drive train	Kevlar Poly V-belt	Data transfer	-
Lenght	106 cm	Brake system	Kevlar break pad	Data display	LCD Console optional
Width	56 cm	Crank hub	Recycled cast iron	Power	If sensor: Batteries
Weight	64 kg	Bearings	High quality SKF bearings	Charge	No

DIMENSIONS

Hight	100 cm / 39 in
Lenght	105 cm / 41 in
Width	60 cm / 23,5 in
Weight	65 kg / 143 lbs
Q-factor	168 mm / 6.6 in
Footprint	0.63 m2 / 6.79 ft2

BIKE TECHNOLOGY

Data display	LCD Console optional
Sensors	-
Power supply	If sensor: Batteries
Charge option	No
Data transfer	If sensor: ANT+

FRAME

Side covers	ABS Plastic
Frame	Robot welded
Front tube	Stainless steel
Sadel tube	Stainless steel
Other frame tubes	Steel

Frame coating Black powder coated

fully protected by side covers

Posts Electro-polished stainless

steel posts

Stabilisers Shot-blasted,

primed and powder coated

Frame mounting Stainless steel

INTERIOR

Drive train	Poly V-belt with Kevlar
Brake system	Friction with kevlar break pad
Crank hub	Processed cast iron, patented
Bearings	High quality SKF bearings
Crank/Pedalarm	Cast iron 170 mm / 6,6 inch
Flywheel	20 kg / 44 lbs cast iron
Emergency brake	Push

TOUCH POINTS

Handelbar	Powder coated stainless steel rubber-coated	
Aerobars	Black aluminium, extended version	
Levelling feet	Adjustable rubber feet stainless steel fitting	
	146:1-1	

Transport wheelsWith heavy duty bearingsAdjustmentsVertical & horizontalBike fitRegular bike fit

Saddle PRO Soft
Thumb screw Yes

Bottle holder "Wave" fits two bottles

Adjustment handles Large handles with stainless steel thread

Service hatch Coin-lock system

Stretch area Reinforced stretch area at the rear end of bike

Pedals SPD, SPD/Look, Standard

COLOR & STYLING

Signature styling optionSimple logo / full hatch

Full colour





